

Brocade BR-1860-2F00 Gegevensblad



Brocade BR-1860-2F00 Dual poort 16Gbps Fibre Channel HBA, SWL SFP+ inbegrepen

BR-1860-2F00

Specificaties

- Merknaam: brocaat
- Fabrikant P/N: BR-1860-2F00

- Aantal poorten/kanalen: 2 poorten
- Protocollen: FC/DCB/FCoE/iSCSI
- Gegevensoverdrachtsnelheid: 16/8/4/2 Gbps
- Bustype: PCI Express 2.0 x8

Ondersteuning van het besturingsysteem

- VMware ESX 3.5
- VMware ESX/ESXi 4.0, U1, U2
- VMware ESX/ESXi 4.1, U1
- VMware ESXi 5.0
- VMware ESXi 5.1
- VMware ESXi 5.5
- Microsoft Hyper-V Server 2008
- Citrix XenServer 6.1
- Oracle VM 3.1.1 (of hoger)

- Windows Server 2008 SP1/SP2 (32-bits)
- Windows Server 2008 SP1/SP2/R2 (64-bits)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (32-bits)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (64-bits)
- Windows Server Core (32/64-bits)
- Windows PE (32-bits)
- Windows PE (64-bits)
- Windows Server 2012 (64-bits)
- Windows Server 2012 R2 (64-bits)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (32-bits)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (64-bits)
- Xen voor RedHat Enterprise Linux 5
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (32-bits)
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (64-bits)
- Red Hat Enterprise Linux 5.2, 5.3 (IA64-bits)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (32-bits)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (64-bits)
- RedHat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (32-bits)
- Red Hat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (64-bits)
- Xen voor SUSE Linux Enterprise Server 10
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (32-bits)
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (64-bits)
- SUSE Linux Enterprise Server 10.3, 10.4 (32-bits)
- SUSE Linux Enterprise Server 10.3, 10.4 (64-bits)
- Xen voor SUSE Linux Enterprise Server 11 (32/64-bits)
- KVM voor SUSE Linux Enterprise Server 11 (32/64-bits)
- SUSE Linux Enterprise Server 11, SP1 (32-bits)
- SUSE Linux Enterprise Server 11, SP1 (64-bits)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (32-bits)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (64-bits)
- Solaris 10 x86 (32-bits)
- Solaris 10 x86 (64-bits)
- Solaris 10 SPARC (64-bits)
- Solaris 11 x86 (64-bits)
- Solaris 11 SPARC (64-bits)
- VMware ESX 4.1 (64-bits)
- VMware ESX 5.0, 5.1 (64-bits)

- Oracle Enterprise Linux 5.7, 5.8 (32-bits)
- Oracle Enterprise Linux 5.7, 5.8 (64-bits)
- Oracle Enterprise Linux 6.1, 6.2 (32-bits)
- Oracle Enterprise Linux 6.1, 6.2 (64-bits)

Media-ondersteuning

- Brokaat 8Gb SFP+, SWL (XBR-000147, XBR-000163)
- Brokaat 8Gb SFP+, LWL, 10Km (XBR-000153)
- Brokaat 16Gb SFP+, SWL (XBR-000192)
- Brokaat 16Gb SFP+, LWL 10Km (XBR-000198)

Data papier

- BR-1860-2F00 Gegevensblad

[Koop.nu](#)