

# Brocade BR-1860-2P00 Gegevensblad



Brocade BR-1860-2P00 Dual Port 10Gb FCoE CNA, inclusief twee 10GbE SR SFP+

BR-1860-2P00

## Specificaties

- Merknaam: brocaat
- Onderdeelnummer: BR-1860-2P
- Fabrikant P/N: BR-1860-2P00
- Aantal poorten/kanalen: 2 poorten
- Protocollen: FCoE
- Gegevensoverdrachtsnelheid: 10 Gbps
- Bustype: PCI Express 2.0 x8

## Ondersteuning van het besturingsysteem

- VMware ESX 3.5
- VMware ESX/ESXi 4.0, U1, U2
- VMware ESX/ESXi 4.1, U1
- VMware ESXi 5.0
- VMware ESXi 5.1
- Vmware ESXi 5.5
- Microsoft Hyper-V Server 2008
- Citrix XenServer 6.1
- Oracle VM 3.1.1 (of hoger)

- Windows Server 2008 SP1/SP2 (32-bits)
- Windows Server 2008 SP1/SP2/R2 (64-bits)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (32-bits)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (64-bits)
- Windows Server Core (32/64-bits)
- Windows PE (32-bits)
- Windows PE (64-bits)
- Windows Server 2012 (64-bits)
- Windows Server 2012 R2 (64-bits)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (32-bits)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (64-bits)
- Xen voor RedHat Enterprise Linux 5
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (32-bits)
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (64-bits)
- Red Hat Enterprise Linux 5.2, 5.3 (IA64-bits)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (32-bits)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (64-bits)
- RedHat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (32-bits)
- Red Hat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (64-bits)
- Xen voor SUSE Linux Enterprise Server 10
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (32-bits)
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (64-bits)
- SUSE Linux Enterprise Server 10.3, 10.4 (32-bits)
- SUSE Linux Enterprise Server 10.3, 10.4 (64-bits)
- Xen voor SUSE Linux Enterprise Server 11 (32/64-bits)
- KVM voor SUSE Linux Enterprise Server 11 (32/64-bits)
- SUSE Linux Enterprise Server 11, SP1 (32-bits)
- SUSE Linux Enterprise Server 11, SP1 (64-bits)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (32-bits)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (64-bits)
- Solaris 10 x86 (32-bits)
- Solaris 10 x86 (64-bits)
- Solaris 10 SPARC (64-bits)
- Solaris 11 x86 (64-bits)
- Solaris 11 SPARC (64-bits)
- VMware ESX 4.1 (64-bits)
- VMware ESX 5.0, 5.1 (64-bits)

- Oracle Enterprise Linux 5.7, 5.8 (32-bits)
- Oracle Enterprise Linux 5.7, 5.8 (64-bits)
- Oracle Enterprise Linux 6.1, 6.2 (32-bits)
- Oracle Enterprise Linux 6.1, 6.2 (64-bits)

## Media-ondersteuning

- Brocade 10Gb SFP+ optische module, SR (XBR-000180)
  
- Brocade 10Gb SFP+ optische module, LR, 10Km (XBR-000182)
- Brocade 10Gb SFP+ optische module, USR (10G-SFPP-USR)
- Brocade 10Gb SFP+ direct-attach (Twinax) kabel, 1m (XBR-TWX-0101)
- Brocade 10Gb SFP+ direct-attach (Twinax) kabel, 3m (XBR-TWX-0301)
- Brocade 10Gb SFP+ direct-attach (Twinax) kabel, 5m (XBR-TWX-0501)
- Cisco 10Gb SFP+ Direct Attach (Twinax)-kabel, 7 m (SFP-H10GB-ACU7M)\*
- Cisco 10Gb SFP+ Direct Attach (Twinax)-kabel, 10 m (SFP-H10GB-ACU10M)\*
- EMC 10Gb SFP+ direct-attach (Twinax) kabel, 1m (SFP-TWNACT-1M, 038-004-176, 038-003-775)
- EMC 10Gb SFP+ direct-attach (Twinax)-kabel, 3 m (SFP-TWNACT-3M, 038-004-177, 038-003-777)
- EMC 10Gb SFP+ direct-attach (Twinax)-kabel, 5 m (SFP-TWNACT-5M, 038-004-178, 038-003-779)

## Data papier

- [BR-1860-2P00 Gegevensblad](#)

[Koop nu](#)